

MaxiPoint™

Description

MaxiPoint™ is a viscous, ready to use roof pointing mortar that is easy to use and very durable. MaxiPoint™ is available in a range of colors to suit new and renovated roofs.

Typical Properties

Appearance:	Colored mortar mix
Flammability/Hazard:	Non flammable, Non hazardous
Clean UP/Thinning:	Water
Per Cent Volatiles:	Zero
Specific Gravity:	1.4
Minimum Film Forming Temperature:	50°F.
Coverage:	1/8" to 3/16" maximum recommended thickness 70'6" to 80'4" linear feet of ridge per 2.64 Gallons (10 litres pail) of MaxiPoint on average
Drying Time:	30 minutes at 70°F
Packaging Sizes:	2.64 Gallons (10 litres)

Applications & Features

Permanently Flexible

Manufactured from a pure grade internally flexibilized acrylic resin to provide permanent flexibility over a wide temperature range and diverse weather conditions.

Smooth to Trowel

Because MaxiPoint does not contain sticky thickeners and the fillers are specially graded to optimize trowel ability, improve application and finishing properties.

Fast Drying

The high resin solids formula of MaxiPoint means less water evaporation required during curing compared to competition products. In very cold and/or moist weather conditions the drying time can be further accelerated, by adding 45 oz of cement, per 2.64 Gallon (10 litres pail) of MaxiPoint. Stir in cement thoroughly. Unused product will set hard quickly and cannot be saved and re-used. Do not add water to retard the curing of MaxiPoint after the addition of the cement.



MaxiPoint™

Fade Resistant

The pure grade acrylic and high quality pigments in MaxiPoint are resistant to UV light damage and moisture which would otherwise cause fading and loss of durability.

Paintable

MaxiPoint can be easily painted with any MaxiPoint water based polymer primer or top coating system

Application Guidelines

MaxiPoint is formulated to feel and towel like a conventional sand and cement mortar. Application by trowel of a thin film between 1/8" to 3/16" thick is recommended using a similar technique to conventional pointing mixes. Wet sponge finishing is not recommended.

New Tile Roofs

Mortar should be finished plumb and free of holes and voids. Fresh bedding does not require full curing before application of MaxiPoint, however, it should be dry enough to resist trowel pressure.

Old Tile Roofs

Cracked or loose unstable bedding and pointing should be replaced. Where pointing over sound old bedding, the surface must be clean and free of dirt, moss, lichen and other contamination. MaxiPoint cannot be expected to adhere unless the substrate is sound and clean. Any existing cement collars should be removed and the roof re-pointed with new cement collars as required.

Shelf Life

Provided cement has not been added to the product a properly sealed or re-sealed pail is expected to have a shelf life of 1 year from the date of manufacture.

Available Colors



MaxiPoint™

Important Application and Usage Warnings

Product must be stored indoors and out of direct sunlight.

Avoid rain for a minimum of 24 hours after application @ 68°F to ensure full curing. In very cold weather the use of MaxiPoint Accelerator available in 2.11 Pint spray bottles and 5 Gallon containers will improve surface curing to resist cold weather and moisture.

Prevent MaxiPoint from freezing in storage.

Storage temperatures should not be below 37°F or above 115.

Warranty

MaxiPoint is guaranteed to resist normal occurring roof movements for 7 years without cracking or breaking away when used over PMM TileTite lightweight bedding compound, MaxiPoint is warranted when used over established sand, cement & oxide pointing admixtures for 3 years.

MaxiPoint warrants its products to be free from defects in material and workmanship. MaxiPoint's sole obligation and Buyer's exclusive remedy in connection with the products shall be limited, at MaxiPoint's option, to either replacement of products not conforming to this Warranty or credit to Buyer's account in the invoiced amount of the nonconforming products.

Any claim under this Warranty must be made by Buyer to MaxiPoint in writing within five (5) days of Buyer's discovery of the claimed defect, but in no event later than the expiration of the applicable shelf life, or one year from the delivery date, whichever is earlier. Buyer's failure to notify MaxiPoint of such non-conformance as required herein shall preclude Buyer from recovery under this Warranty.

MaxiPoint makes no other warranties concerning the product. No other warranties, whether express, implied, or statutory, such as warranties of merchantability or fitness for a particular purpose, shall apply. In no event shall MaxiPoint be liable for consequential or incidental damages.



MaxiPoint™

Any recommendation or suggestion relating to the use of the products made by MaxiPoint, whether in technical literature, or in response to specific inquiry, or otherwise, is based on data believed to be reliable; however, the products and information are intended for use by Buyers having requisite skill and know-how in the industry, and therefore it is for Buyer to satisfy itself of the suitability of the products for its own particular use and it shall be deemed that Buyer has done so, at its sole discretion and risk. Variation in environment, changes in procedures of use, or extrapolation of data may cause unsatisfactory results.

Limitation of Liability

MaxiPoint's liability on any claim of any kind, including claims based upon MaxiPoint's negligence or strict liability, for any loss or damage arising out of, connected with, or resulting from the use of the products, shall in no case exceed the purchase price allocable to the products or part thereof which gives rise to the claim. In no event shall MaxiPoint be liable for consequential or incidental damages.

