

# Safety Data Sheet Revision Date: 05/31/2019

# SECTION 1: Identification and Company Details

Product Name: Product Code:	Marquis Base Mix 050400
Manufacturer/ Supplier: Address:	Premix Marbletite 1259 N.W. 21st Street Pompano Beach, FL 33069
Emergency Phone: Product Information:	(800) 424-9300 (24-hour Response / CHEMTREC) 800-432-5097
Recommended Use:	Pool Plaster
SECTION 2: Hazard	(s) Identification
OSHA / HCS Status:	This product is classified as hazardous under GHS criteria.
GHS Ratings: Carcinogen Oral Toxicity Skin Irritation Eye damage Skin sensitization Signal Word: Hazard Statements:	1A       Known Human Carcinogen Based on human evidence         Acute Tox. 4       Oral>300+<=2000mg/kg
Hazard Pictograms:	
Precautionary Statements:       Obtain special instructions before use.         Do not handle until all safety precautions have been read and understood.         Do not breathe dust/fume/gas/mist/vapors/spray.         Do not eat, drink, or smoke when using this product.         Wear protective gloves/clothing/eye protection/face protection.         Use personal protective equipment as required.         Wash contaminated clothing before reuse         IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.         IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.         IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.	

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. IF exposed or concerned: Get medical advice/attention Store locked up.Dispose of contents/container in accordance with local authority requirements. Incineration is the preferred method of disposal.

SECTION 3:	Composition / Information on Ingredients	Weight %	CAS #
	Quartz	50 - 65%	14808-60-7
	Cement, portland, chemicals	30 - 40%	65997-15-1
	Marble Dust	< 10 %	1317-65-3
	Proprietary admix	< 5 %	NA
SECTION 4:	First-Aid Measures		
Inhalation:	breathing, if breathing is irregular o oxygen by trained personnel. Risk	or of respiratory arrest occ may occur to the person	able for breathing. If the person is not curs, provide artificial respiration or providing mouth-to-mouth resuscitation. nedical attention immediately. Maintain
Skin Contact:	Wash with soap and water. Remov	ve contaminated clothing	. Consult physician for rashes, burns,
irritation and prolor	nged unprotected exposures to wet cement, c		
	Burns should be treated as causti	c burns. Feeling of pain o	or the severity of the burn may not occur
until hours after the	e exposure. In the event of any complaints or		
Eye Contact:	Flush with copious amounts of wat eyelids. Remove any contact lense		s occasionally lifting upper and lower necessary.
Ingestion:	position comfortable for breathing. If give small quantities of water to drink that vomit does not enter the lungs. (	product has been swallow c. Stop giving water if vomi Chemical burns must be tro s person. If unconscious, p	victim to fresh air and keep at rest in a ed and the exposed person is conscious, ting occurs, the head should be kept low so eated promptly by a physician. Never give place in recovery position and get medical cian.
Note to Physician	•	skin sensitizer. Treat sym hermal burn. There is no specific antio	
	<b>Respiratory:</b> Treatment is essenti exposure and assist in breathing if	ally symptomatic. Remov	

## SECTION 5: Fire-Fighting Measures

 

 Extinguishing Media:
 This product is not flammable. Use fire- extinguishing media appropriate for surrounding materials. Don't use water jet. Suitable extinguishing media - Water and Carbon dioxide (CO2).

 Hazardous Combustion Products:
 May include but not limited to Oxides of Carbon, Sulfur Oxides and Metal Oxides.

 Protection of Firefighters:
 Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

#### SECTION 6: Accidental Release Measures

Personal Precautions:	Use personal protection equipment. Do not breathe dust. Provide adequate ventilation. Use protective gloves, goggles and suitable protective clothing.
Environmental Precautions:	Sweep and transfer dry product to containers. Place wet product in proper containers and allow product to harden. Keep spills and cleaning runoffs out of municipal sewers and open water. Inform specific authorities if the product has entered the environment, including water, drains and soil.

Methods of Clean-up:	<ul> <li>Vacuum with HEPA fitted filter equipment place in a disposal container. Seal securely and deliver for disposal according to local regulations. Wash with plenty of water. Wear necessary protective equipment.</li> <li>Handling and Storage</li> </ul>		
Handling Precautions:	Avoid generating and breathing dust. Avoid contact with skin and eyes. Do not get the product inside boots, shoes or gloves. Wet, saturated clothing should not remain on skin. Appropriate respirator should be worn when ventilation is inadequate. Do not eat, drink or smoke when using the product. Use of compressed air for cleaning clothing, equipment etc. is not recommended. Do not reuse packaging.		
Storage:	Keep separate from food, feedstuffs, fertilizers and other sensitive material. Store in dust tight, dry and labeled closed container. Avoid product contact with skin and eyes. Be Aware- This product may build up or adhere to the walls of a confined space and release or fall suddenly. KEEP OUT OF REACH OF CHILDERN.		
Other:	Every attempt possible should be made to avoid skin/eye contact with Portland cement. Portland Cement will react with water to produce calcium hydroxide, a compound that will potentially cause chemical burns to the user.		
SECTION 8: Exposu	re Control / Personal Protection		
Exposure Guidelines:	Not determined		
Engineering Controls:	•		
or other engineering controls to limit airborne containment.			
Environmental Controls:	Environmental Controls: Emissions from ventilation or work process equipment should comply with the requirements of environmental protection legislation.		
Personal Protective Equip	ment:		
<ul> <li>Skin Protection - Permeation resistant gloves (butyl rubber, nitrile rubber, PVC or polyvinyl alcohol). Do not allow this product inside gloves. Wear high impervious boots, do not get the product inside boots, shoes or gloves. Remove saturated clothing and protective equipment and immediately wash exposed areas of the body.</li> <li>Eye/Face Protection – use chemical splash proof goggle. It's not recommended to use wear contact lenses when working with this product.</li> <li>Respiratory Protection- Use respirator with a filter selected based on known or anticipated</li> </ul>			
exposure levels, hazards of	the product.		
Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure
Limits			,
Quartz	Not Established	0.025 mg/m3 TWA	NIOSH: 0.05 mg/m3
14808-60-7		(respirable fraction)	TWA (respirable dust)
Cement, portland,	15 mg/m3 TWA	1 mg/m3 TWA	NIOSH: 10 mg/m3 TWA
chemicals	(total dust)	(particulate matter containing no	(total dust);
65997-15-1	5 mg/m3 TWA (respirable fraction)	asbestos and <1% crystalline silica, respirable fraction)	5 mg/m3 TWA (respirable dust)
Marble Dust 1317-65-3	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)	Not Established	NIOSH: 10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)

# SECTION 9: Physical and Chemical Properties

Appearance:	White Powder dry and creamy paste when wet
Odor:	Slight, non-offensive odor
Relative Density:	2.30 - 2.70

Odor Threshold:	Not available
Solubility:	Partially Soluble (in water)
pH:	9.30 in water
Partition Coefficient:	Not available
Melting Point:	Not available
Freezing Point:	Not available
Auto-ignition Temperature:	Not available
Flash Point:	Not available
<b>Decomposition Temperatur</b>	re: Not available
Evaporation Rate:	Not available
Viscosity:	Not available
Flammability (Solid/Gas):	Non-Flammable
Upper/Lower Flammability:	Not available
VOC Content:	Not available
Vapor Pressure:	Not available
Boiling Point:	Not available

# SECTION 10: Stability and Reactivity

Chemical Stability:	Stable under normal temperature conditions and recommended use.		
Conditions to Avoid:	Excessive heat, direct sunlight and/or frost.		
Materials to Avoid:	Oxidizing materials, acids, aluminum and ammonium salt. This product is highly alkaline and will react with acids to product harsh, heating- generating reaction. Aluminum powder and other		
alkaline earth			
contact with	elements will react in wet mortar or concrete, liberating hydrogen gas. Limestone ignites on		
	fluorine and is incompatible with acids, alum, ammonium salts, and magnesium.		

## SECTION 11: Toxicological Information

Acute Toxicity:	Oral Toxicity LD50: 834mg/kg
Ingestion:	May cause burns to mouth, throat and stomach.
Inhalation:	May cause respiratory irritation.
Skin Contact:	May cause severe burns. May cause an allergic skin reaction.
Eye Contact:	May cause serious eye damage or irritation.

## **Component Toxicity:**

CAS Number	Description	Carcinogen Rating
14808-60-7	Quartz	Quartz: NIOSH: potential occupational carcinogen
		IARC: Human carcinogen
		OSHA: listed

## SECTION 12: Ecological Information

Mobility and Bioaccumulation Potential:Not determinedDegradation:Not determinedAquatic Toxicity:Not determinedLC50 – 24 hour (Static):Not determined

## SECTION 13: Disposal Considerations

Disposal:	Dispose of waste and residues in accordance with local authority requirements based on the environmental protection and waste disposal legislation. This material and its container must be disposed of in a safe manner. Waste packaging should be recycled. Avoid dispersal of spilled material and runoff, and contact with soil, waterways, drains and sewers.			
Wastes or Residues:	Same as above.	· · ·	, <i>'</i>	
SECTION 14: Transpo	ort Information			
Road:	DOT Proper Shipping Name DOT Packing Group: N/A DOT Label: N/A UN Number: N/A	Non-Regulated		
Ocean:	Proper Shipping Name: <b>Non</b> Sea – IMO/IMDG Class: N/A UN Number: N/A Label: N/A Packing Group: N/A Marine Pollutant: N/A EMS: N/A	•		
Air:	Proper Shipping Name: <b>Nor</b> Air – ICAO/IATA Class: N/A UN Number: N/A Label: N/A Sub Class: N/A Packing Group: N/A Pack Instr. Passenger: N/A Pack Instr. Cargo: N/A	n-Regulated		
SECTION 15: Regulat	tory Information			
Status on Substance Lists: The concentrations shown in this document are maximum levels (weight %) to be used for regulations.				
TSCA:	The components of this prod	luct are contained on th	ne chemical substance	e inventory list.
OSHA:	This product is Hazardous as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.			
OSHA PEL's	14808-60-7 / Crystalline Silica 65997-15-1 / Cement, Portland, chemicals 1317-65-3 / Marble Dust			
Federal EPA:	Comprehensive Environmental Response, Compensation and Liability Act of 1980 (CERCLA): Requires notification of the national response center of release of quantities of hazardous substances equal to or greater than the reportable quantities (RQ's) in 40 CFR 302.4. Components present in this product at level which could require reporting under the statute are:			e of quantities of RQ's) in 40 CFR
	Chemical Name None	CAS Number None	% <b>by Weight</b> None	<b>RQ</b> None

Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III: Sections 301-304 require emergency planning based on Threshold Planning Quantities (TPQs) and release reporting based on Reportable Quantities (RQ) in 40 CFR 355. Components present in this product at level which could require reporting under this statue are:

Chemical Name	CAS Number	% by Weight	RQ
None	None	None	None

Section 311-312 require products be reviewed and applicable EPA Hazard Definitions be identified and made known- **None** 

N.I	RTK
INJ	NIN

14808-60-7 Quartz 1317-65-3 Marble Dust 65997-15-1 Cement, portland, chemicals

#### Pennsylvania RTK

14808-60-7 Quartz 1317-65-3 Marble Dust 65997-15-1 Cement, portland, chemicals

#### Massachusetts RTK

14808-60-7 Quartz 1317-65-3 Marble Dust 65997-15-1 Cement, portland, chemicals

## **EPA Hazard Classifications:**

Acute	Chronic	Fire	Pressure	Reactive
Hazard	Hazard	Hazard	Hazard	Hazard
Yes	Yes	No	No	No

Section 313 requires submission of annual reports of release of toxic chemicals that appear in 40 CFR 372 (for SARA 313). This information must be included in all SDSs that are distributed for this material. Components present in this product at level which could require reporting under the statute are: **None** 

Canada DSL: This material is listed or exempted.

California Proposition 65:Warning: This product contains chemicals known to the State of California to cause cancer.14808-60-7/Crystalline Silica. . For more information on California Proposition 65, go<br/>to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>

#### SECTION 16: Other Information

This Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200).

## HMIS RATING: HEALTH-3, FLAMMABILITY-0, REACTIVITY-0, PERSONAL PROTECTION- E.

## Hazardous Material Information System (HMIS)

Prepared by: Premix Marbletite Product Safety & Regulatory Compliance Group, (800) 432-5097

The information herein is given in good faith, but no warranty expressed or implied is made. Premix Marbletite urges users of this product to evaluate its suitability and compliance with local regulations as Premix Marbletite cannot foresee the final use of the product, nor the final location of usage.

Date of issue: 5/31/2019