

Safety Data Sheet

Revision Date: 5/31/2019

SECTION 1: Identification and Company Details

Product Name: Marquis Tinted

Product Code: 0504"xx" Series – Multiple Codes

Manufacturer/ Supplier: Premix Marbletite
Address: 1259 N.W. 21st Street
Pompano Beach, FL 33069

Emergency Phone: (800) 424-9300 (24-hour Response / CHEMTREC)

Product Information: 800-432-5097

Recommended Use: Pool Plaster

SECTION 2: Hazard(s) Identification

OSHA / HCS Status: This product is classified as hazardous under GHS criteria.

GHS Ratings:

Carcinogen 1A Known Human Carcinogen Based on human evidence

Oral Toxicity Acute Tox. 4 Oral>300+<=2000mg/kg

Skin Irritation 2
Eye damage 1
Skin sensitization 1

Signal Word: Danger

Hazard Statements: Harmful if swallowed

May cause cancer

Hazard Pictograms:







Precautionary Statements: Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash hands thoroughly after handling.

Do not eat, drink, or smoke when using this product.

Wear protective gloves/clothing/eye protection/face protection.

Use personal protective equipment as required. Specific treatment- treat symptomatically. Wash contaminated clothing before reuse.

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with

water/shower.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present

and easy

to do – continue rinsing. IF exposed or concerned: Get medical advice/attention.

Store locked up.

Dispose of contents/container in accordance with local authority requirements. Incineration is the

preferred

method of disposal.

SECTION 3:	Composition / Information on Ingredients	Weight %	CAS#	
	Quartz	50 - 70%	14808-60-7	
	Cement, portland, chemicals	20 - 40%	65997-15-1	
	Marble Dust	< 10%	1317-65-3	

SECTION 4: First-Aid Measures

Inhalation: Move victim to fresh air and keep at rest in position comfortable for breathing. If the person is not

breathing, if breathing is irregular or of respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Risk may occur to the person providing mouth-to-mouth resuscitation. If victim is unconscious, place in recovery position and get medical attention immediately. Maintain

an open airway.

Skin Contact:

irritation,

Wash with soap and water. Remove contaminated clothing. Consult physician for rashes, burns,

and prolonged unprotected exposures to wet cement, cement mixtures or liquids from wet cement. Burns should be treated as caustic burns. Feeling of pain or the severity of the burn may not occur

until

hours after the exposure. In the event of any complaints or symptoms, avoid further exposure.

Eye Contact: Flush with copious amounts of water for at least 15 minutes occasionally lifting upper and lower

eyelids. Remove any contact lenses. Consult physician if necessary.

Ingestion: Do not induce vomiting. Wash mouth with water. Remove victim to fresh air and keep at rest in a

position comfortable for breathing. If product has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop giving water if vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give

anything by mouth to an

unconscious person. If unconscious, place in recovery position and get medical attention immediately.

Maintain an

open airway. Consult physician.

Note to Physician: Eyes: Stain for evidence of corneal injury. If cornea is burned, instill antibiotic steroid preparation.

Skin: This compound is a known skin sensitizer. Treat symptomatically as for contact dermatitis or

thermal burns. If burned, treat as thermal burn.

Ingestion: Treat symptomatically. There is no specific antidote. Inducing vomiting is

contraindicated because of the irritating nature of this compound.

Respiratory: Treatment is essentially symptomatic. Remove individual with symptoms from

exposure and assist in breathing if necessary.

SECTION 5: Fire-Fighting Measures

Extinguishing Media: This product is not flammable. Use fire- extinguishing media appropriate for surrounding materials.

Don't use water jet. Suitable extinguishing media - Water and Carbon dioxide (CO2).

Hazardous Combustion Products: May include but not limited to Oxides of Carbon, Sulfur Oxides and Metal Oxides.

Protection of Firefighters: Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

SECTION 6: Accidental Release Measures

Personal Precautions: Use personal protection equipment. Do not breathe dust. Provide adequate ventilation. Use

protective gloves, goggles and suitable protective clothing.

Environmental Precautions: Sweep and transfer dry product to containers. Place wet product in proper containers and allow

product to harden. Keep spills and cleaning runoffs out of municipal sewers and open water. Inform specific authorities if the product has entered the environment, including water, drains and soil. Vacuum with HEPA fitted filter equipment place in a disposal container. Seal securely and deliver

for disposal according to local regulations. Wash with plenty of water. Wear necessary protective

equipment.

SECTION 7: Handling and Storage

Methods of Clean-up:

Handling Precautions: Avoid generating and breathing dust. Avoid contact with skin and eyes. Do not get the product inside

boots, shoes or gloves. Wet, saturated clothing should not remain on skin. Appropriate respirator should be worn when ventilation is inadequate. Do not eat, drink or smoke when using the product. Use of compressed air for cleaning clothing, equipment etc. is not recommended. Do not reuse

packaging.

Storage: Keep separate from food, feedstuffs, fertilizers and other sensitive material. Store in dust tight, dry

and labeled closed container. Avoid product contact with skin and eyes. Be Aware- This product

may build up or adhere to the walls of a confined space and release or fall suddenly.

KEEP OUT OF REACH OF CHILDERN.

Other: Every attempt possible should be made to avoid skin/eye contact with Portland cement.

Portland Cement will react with water to produce calcium hydroxide, a compound that will potentially

cause chemical burns to the user.

SECTION 8: Exposure Control / Personal Protection

Exposure Guidelines: Not determined

Engineering Controls: Provide adequate ventilation. If dust accumulated, use process enclosures, local exhaust ventilation

or other engineering controls to limit airborne containment.

Environmental Controls: Emissions from ventilation or work process equipment should comply with the requirements of

environmental protection legislation.

Personal Protective Equipment:

Skin Protection - Permeation resistant gloves (butyl rubber, nitrile rubber, PVC or polyvinyl alcohol). Do not allow this product inside gloves. Wear high impervious boots, do not get the product inside boots, shoes or gloves. Remove saturated clothing and protective equipment and immediately wash exposed areas of the body.

Eye/Face Protection – use chemical splash proof goggle. It's not recommended to use wear contact lenses when working with this product.

Respiratory Protection- Use respirator with a filter selected based on known or anticipated

exposure levels, hazards of the product.

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure
<u>Limits</u>			
Cement, portland,	15 mg/m3 TWA	1 mg/m3 TWA	NIOSH: 10 mg/m3 TWA
chemicals	(total dust)	(particulate matter containing no	(total dust);
65997-15-1	5 mg/m3 TWA (respirable fraction)	asbestos and <1% crystalline silica, respirable fraction)	5 mg/m3 TWA (respirable dust)
Quartz 14808-60-7	Not Established	0.025 mg/m3 TWA (respirable fraction)	NIOSH: 0.05 mg/m3 TWA (respirable dust)

Marble Dust	15 mg/m3 TWA (total dust); 5		NIOSH: 10 mg/m3 TWA
1317-65-3	mg/m3 TWA (respirable	Not Established	(total dust); 5 mg/m3
	fraction)		TWA (respirable dust)

SECTION 9: Physical and Chemical Properties

Appearance: White Powder with dry pigment **Odor:** Slight, non-offensive odor

Relative Density: 2.65 - 2.95 **Odor Threshold:** Not available

Solubility: Partially Soluble (in water)

pH: 9.30 in water **Partition Coefficient:** Not available **Melting Point:** Not available Freezing Point: Not available Auto-ignition Temperature: Not available Flash Point: Not available **Decomposition Temperature:** Not available **Evaporation Rate:** Not available Viscosity: Not available Flammability (Solid/Gas): Non-Flammable Upper/Lower Flammability: Not available **VOC Content:** Not available Vapor Pressure: Not available **Boiling Point:** Not available

SECTION 10: Stability and Reactivity

Chemical Stability: Stable under normal temperature conditions and recommended use.

Conditions to Avoid: Excessive heat, direct sunlight and/or frost.

Materials to Avoid: Oxidizing materials, acids, aluminum and ammonium salt. This product is highly alkaline and will

react with acids to product harsh, heating- generating reaction. Aluminum powder and other

alkaline earth elements will react in wet mortar or concrete, liberating hydrogen gas. Limestone ignites on contact with

fluorine and is incompatible with acids, alum, ammonium salts, and magnesium.

SECTION 11: Toxicological Information

Acute Toxicity: Oral Toxicity LD50: 809mg/kg

Ingestion: May cause burns to mouth, throat and stomach.

Inhalation: May cause respiratory irritation.

Skin Contact: May cause severe burns. May cause an allergic skin reaction.

Eye Contact: May cause serious eye damage or irritation.

Component Toxicity:

CAS Number Description Carcinogen Rating

14808-60-7 Quartz Quartz: NIOSH: potential occupational carcinogen

IARC: Human carcinogen

OSHA: listed

SECTION 12: Ecological Information

Mobility and Bioaccumulation Potential: Not determined

Degradation: Not determined Aquatic Toxicity: Not determined LC50 – 24 hour (Static): Not determined

SECTION 13: Disposal Considerations

Disposal: Dispose of waste and residues in accordance with local authority requirements based on the

environmental protection and waste disposal legislation. This material and its container must be disposed of in a safe manner. Waste packaging should be recycled. Avoid dispersal of spilled

material and runoff, and contact with soil, waterways, drains and sewers.

Wastes or Residues: Same as above.

SECTION 14: Transport Information

Road: DOT Proper Shipping Name: Non-Regulated

DOT Packing Group: N/A

DOT Label: N/A UN Number: N/A

Ocean: Proper Shipping Name: Non-Regulated

Sea - IMO/IMDG Class: N/A

UN Number: N/A Label: N/A

Packing Group: N/A
Marine Pollutant: N/A

EMS: N/A

Air: Proper Shipping Name: Non-Regulated

Air - ICAO/IATA Class: N/A

UN Number: N/A Label: N/A Sub Class: N/A Packing Group: N/A Pack Instr. Passenger: N/A Pack Instr. Cargo: N/A

SECTION 15: Regulatory Information

Status on Substance Lists: The concentrations shown in this document are maximum levels (weight %) to be used for

regulations.

TSCA: The components of this product are contained on the chemical substance inventory list.

OSHA: This product is Hazardous as defined by the OSHA Hazard Communication Standard, 29

CFR 1910.1200.

OSHA PEL's 1317-65-3 Marble Dust

14808-60-7 Quartz

65997-15-1 Cement, portland, chemicals

Federal EPA:

Comprehensive Environmental Response, Compensation and Liability Act of 1980 (CERCLA): Requires notification of the national response center of release of quantities of hazardous substances equal to or greater than the reportable quantities (RQ's) in 40 CFR 302.4. Components present in this product at level which could require reporting under the statute are:

Chemical Name CAS Number % by Weight RQ
None None None None
Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III: Sections 301-304
require emergency planning based on Threshold Planning Quantities (TPQs) and release reporting

based on Reportable Quantities (RQ) in 40 CFR 355. Components present in this product at level which could require reporting under this statue are:

Chemical NameCAS Number% by WeightRQNoneNoneNoneNone

Section 311-312 require products be reviewed and applicable EPA Hazard Definitions be identified and made known- **None**

NJ RTK

1317-65-3 Marble Dust 14808-60-7 Quartz 65997-15-1 Cement, portland, chemicals

Pennsylvania RTK

1317-65-3 Marble Dust 14808-60-7 Quartz 65997-15-1 Cement, portland, chemicals

Massachusetts RTK

1317-65-3 Marble Dust 14808-60-7 Quartz 65997-15-1 Cement, Portland, chemicals

EPA Hazard Classifications:

AcuteChronicFirePressureReactiveHazardHazardHazardHazardHazardYesYesNoNoNo

Section 313 requires submission of annual reports of release of toxic chemicals that appear in 40 CFR 372 (for SARA 313). This information must be included in all SDSs that are distributed for this material. Components present in this product at level which could require reporting under the statute are: **None**

Canada DSL: This material is listed or exempted.

California Proposition 65: Warning: This product contains chemicals known to the State of California to cause cancer.14808-

60-7/Crystalline Silica. For more information on California Proposition 65, go to

www.P65Warnings.ca.gov

SECTION 16: Other Information

This Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200).

HMIS RATING: HEALTH-3, FLAMMABILITY-0, REACTIVITY-0, PERSONAL PROTECTION- E.

Hazardous Material Information System (HMIS)

Prepared by: Premix Marbletite Product Safety & Regulatory Compliance Group, (800) 432-5097

The information herein is given in good faith, but no warranty expressed or implied is made. Premix Marbletite urges users of this product to evaluate its suitability and compliance with local regulations as Premix Marbletite cannot foresee the final use of the product, nor the final location of usage.

Date of issue: 5/31/2019